

Panasonic

SP 2G / Splash Proof





I Series Lineup

Specification

Rated Voltage	200-240V
Frequency	50/60Hz
Lifetime	25,000 hours
CRI	80
Ambient Temperature	-20°C~40°C
Power Factor	0.9
Materials	Body: PC(White) Reflector: PC
IP Rating	IP65
Surge Protection	1kVA



Dimension

2FT



Size : 600×70×50mm
Weight : 1.0kg

4FT



Size : 1212×70×50mm
Weight : 2.1kg

5FT



Size : 1500×70×50mm
Weight : 3.1kg

SP 2G Splash Proof



Long Lifetime
25,000H




CRI
80



High Efficacy
100-111lm/W



IP Rating
IP65



Power Factor
0.9



Ambient Temperature
-20°C~40°C

I Data

Type	2FT (600mm)	4FT (1212mm)	5FT (1500mm)	
Wattage	18W	36W	45W	
Non Dimming	4000K ●	NNFC4033088 1800lm, 100lm/W	NNFC4033188 3600lm, 100lm/W	NNFC4033288 5000lm, 111lm/W
	6500K ●	NNFC4038088 1800lm, 100lm/W	NNFC4038188 3600lm, 100lm/W	NNFC4038288 5000lm, 111lm/W
Photometric Distribution				

cd/klm (l=100%)
— C0, C180
— C90, C270

Certification



RoHS

CISPR15



Panasonic Lighting - Product Quality Testing



Learn more about Panasonic's successful installations



Please contact

<https://panasonic.net/electricworks/lighting/>



Panasonic[®]

All Rights Reserved © 2021 COPYRIGHT Panasonic Corporation Electric Works Company